

LRAD 100X BLK MAG SYS

Long Range Communication with Wireless Kit



PRODUCT INFORMATION

100X-BLK-MAG-SYS LRAD 100X MAG-HS system includes magnetic base with 600 lbs. of holding and 120 lbs. of shear force*, and accompanying mounting yoke to secure the LRAD to metallic surfaces, including vehicle roofs

INCLUDED ACCESSORIES

| MP3 Player | MP3 player records/plays up to 8GB of messages and tones |
|-----------------------|---|
| Wireless Kit | Wireless operation of LRAD systems over ranges up to 200 meters, 35mm phone jack connects to a standard MP3 audio device (UHF, US only). Lightweight hypercardioid headset microphone is included |
| Record on the Fly Mic | Microphone with record and playback feature for immediate playback |
| MP3 Auxiliary Cable | Allows connection to any audio device with a headphone jack |
| USB Cable | USB cable for downloading files to the MP3 player |
| Li-Fe-PO4 Battery | 8-Hour Lithium Iron Phosphate rechargeable battery |
| Battery Charger | AC powered battery charger with LED battery charge status display |
| Hard Case | Watertight, dust proof, rugged enclosure for storage and transport |

OPTIONAL ACCESSORIES

| HD Action Camera | During LRAD operation, record High Definition, date/time stamped video and audio with this compact, rugged digital camera |
|------------------------------|---|
| AC Power Supply | Can be powered by a standard AC source in place of the battery |
| Cigarette lighter/plug cable | Cigarette lighter/plug cable powers LRAD through 12 VDC cigarette lighter |
| Stud Mount | Mounting yoke kit for LRAD-100X, compatible for LRAD tripods (tripod not included) |
| Stud Kit | Stud weldment kit |
| Medium-Duty Tripod Kit | Includes reusable hard case |
| Table Mount Kit | Fixed mount for flat surfaces |
| Tactical Pack | Rugged backpack for operation of the LRAD 100X within the pack or on the move |
| Front Carry Pack | For mobile or stationary operation of the LRAD 100X |
| VAC Mount | Mounts LRAD 100X on most smooth or slightly curved nonporous surfaces |

DIRECTIONALITY, POWER, RANGE & INTELLIGIBILITY

- Powerful, intelligible voice communications up to 600 meters
- Focused, directional broadcasts for targeted communication
- Safely communicate beyond standoff distances
- Create instant acoustic standoff perimeter
- Deliver clearly heard and understood communications into buildings & vehicles

FEATURES

- > 8-hour rechargeable battery
- Operate easily with gloves or MOPP gear
- Optional power sources
- > Simple operator interface
- > Water resistant
- HD Camera (optional) Quick connect/disconnect camera and mount for recording video and audio during LRAD operation. Includes 4GB micro SDHC for up to 210 minutes of date and time stamped recordings

MARKETS SERVED

- > Law Enforcement
- > Defense
- Commercial Security
- › Critical Infrastructure Security
- Maritime
- > Homeland & Border Security
- › Fire Rescue & Incident Management
- > Emergency Warning
- Mass Communication
- › Wildlife Preservation & Asset Protection

*Combined force and shear ratings of mag mount for 1/4" unfinished steel. Painted surfaces and thinner metals will have less holding and shear force.



LRAD 100X BLK MAG SYS

Long Range Communication with Wireless Kit

SELF-CONTAINED, PORTABLE **COMMUNICATION SYSTEM**

The LRAD 100X MAG-HS System consists of an LRAD 100X, a mount with four high strength magnets that clamp to, and unclamp from, magnetic surfaces with a turn of a knob, an LRAD Wireless Kit for remote operation, an AC-powered battery charger, an MP3 player with an all-weather record-on-the-ly mic, a watertight, dust proof hard case, and other accessories.

With unparalleled vocal clarity and up to 30db louder than bullhorns, megaphones, and vehicle P.A. systems, the LRAD 100X is also four to six times louder than other acoustic hailers of comparable size and weight. LRAD's optimized driver and waveguide technology ensures every message is clearly broadcast, heard and understood, even above engine, crowd, siren, and background noise.

The LRAD warning tone commands attention to the voice messages that follow and provides a safer alternative to non-lethal and kinetic measures for changing behavior.



ACOUSTIC PERFORMANCE

| Maximum Peak Output | 140dB SPL @ 1 meter, C-weighted |
|---------------------------|--|
| Maximum Continuous Output | 137db SPL @ 1 meter, A-weighted |
| Sound Projection | +/- 15° @ 1kHz/-3dB |
| Communication Ranges | Maximum range up to 600 meters in ideal conditions. Operational range up to 250 meters over 88dB of background noise. Ranges based on continuous output. |

ENVIRONMENTAL PERFORMANCE¹

| 1800 | |
|------|-----|
| | |
| | NIS |
| | |

| Hot Operating Temperature | MIL-STD-810G, Method 501.5, Procedure II, Design type Hot, 60°C |
|----------------------------|---|
| Cold Operating Temperature | MIL-STD-810G, Method 502.5, Procedure II, Design type Basic Cold, -33°C |
| Hot Storage Temperature | MIL-STD-810G, Method 501.5, Procedure I, 70°C |
| Cold Storage Temperature | MIL-STD-810G, Method 502.5, Procedure I, -40°C |
| Operating Humidity | MIL-STD 810G, Method 507.5, Procedure II – Aggravated Cycle |
| Rain | MIL-STD-810G, Method 506.5, Procedure I, Blowing rain |
| Salt Fog | MIL-STD-810G, Method 509.5 |
| Shipboard Vibration | MIL-STD-167-1A |
| Shipboard Shock | MIL-S-901D, Class I, Shock grade B |
| Random Vibration | MIL-STD-810G, Method 516.6, Procedure I, (Functional shock) |
| | |

¹TESTED BY NATIONAL TECHNICAL SYSTEMS (NTS) FOLLOWING MIL-STD-810G, MIL-STD-167-1A & MIL-S-901D.

MECHANICAL

| Dimensions | 17"W x 21"H x 9"D (43 x 53x 23 cm) |
|--------------|---|
| Weight | 22 lbs.(10 kg) with battery, accessories and cables |
| Construction | Injection molded, impact resistant polymer, 6061 Aluminum |

ELECTRICAL REQUIREMENTS²

| Power Consumption | Typical Power consumption 85 Watts (With tone) Normal power consumption 20 Watts (With voice content) |
|-------------------|---|
| Power Input | 10.8 to 16.8 VDC, Included rechargeable 13.2 VDC Li-Fe-PO battery for up to 2 hours of continuous operation at maximum volume on a full charge. |

BATTERY LIFE UP TO 2 HOURS OF CONTINUOUS OPERATION AT MAXIMUM TONE ON A FULL CHARGE. ADAPTERS AVAILABLE FOR AUTO CIGARETTE LIGHTER AND FOR 2590 RECHARGEABLE MILITARY BATTERY.

SAFETY³

MIL-STD-1474D

3MIL-STD-1474D STANDARD ESTABLISHES ACOUSTICAL NOISE LIMITS AND PRESCRIBES TESTING REQUIREMENTS AND MEASUREMENT TECHNIQUES FOR DETERMINING CONFORMANCE TO THE NOISE LIMITS SPECIFIED THEREIN.

ELECTROMAGNETIC COMPATIBILITY (EMC)⁴

FCC Part 15 class A radiated emissions, CE

 ϵ

FROUIREMENTS FOR THE CONTROL OF ELECTROMAGNETIC INTERFERENCE CHARACTERISTICS OF SUBSYSTEMS AND EQUIPMENT.



Genasys - The Leader in Protective Communications

Genasys Protective Communications Solutions have a diverse range of applications, including predictive

simulation to anticipate and understand the potential impact of emerging crises; emergency warning and mass notification for public safety; critical event management

for commercial enterprises and government agencies; deescalation for defense and law enforcement; as well as automatic detection of real-time threats.

For more information, visit genasys.com.





