



Dash Mount Control Module (MP3 Player)

Record-on-the-fly Microphone

PRODUCT INFORMATION

450XL (-BLK/-GRN/-GRY/-TAN)	LRAD 450XL manually operated, long range communication system with dash mounted MP3 control module
-----------------------------	--

INCLUDED ACCESSORIES

Control Module	Remote MP3 control module
Record-on-the-fly Mic	Microphone with record and playback feature for immediate playback
MP3 Auxiliary Cable	Allows connection to any audio device with a headphone jack
USB Cable	USB cable for downloading files to the MP3 player
Hearing Protection	Disposable hearing protection
Normalizer Software	Normalizer software for creating customized audio recordings on a PC
Tripod Adapter	Allows for mounting on optional tripod
Hard Case	Watertight, dust proof, rugged enclosure for storage and transport

OPTIONAL ACCESSORIES

Wireless Kit	Wireless transmitter, receiver, and headset that allows remote use of LRAD systems over ranges up to 200 meters
HD Action Camera	During LRAD operation, record high definition, date/time stamped video and audio with this compact, rugged digital camera
Magnetic Mount Kit	Magnetic base and accompanying mounting yoke to secure the LRAD to metallic surfaces including vehicle roofs
Maxabeam Kit	12 million candlepower in a lightweight, mounted searchlight that illuminates targets up to 3,500 meters away
Power Supply Module	External AC to DC power supply, 100-220 VAC to 28 VDC
Power Pack	Portable power pack with internal battery, charger, 24 VDC, 21 AH
Hitch Mount	Vehicle Mount - attaches to standard trailer hitch receiver (2 in/5.08cm)
GPK Mount	Mounts to Objective Gunner Protection Kit (OGPK) for vehicle mounted operations
Ship Rail Mount	Stainless steel rail mount
Table Mount	Flat surface mount
Medium Duty Tripod	Rugged lightweight tripod with optional hard transport and storage case

DIRECTIONALITY, POWER, & RANGE

- > Powerful, intelligible voice communication up to 1,700 meters
- > Focused, directional broadcasts for targeted communications
- > Communicate safely beyond standoff distances
- > Create instant acoustic standoff perimeter
- > Variable beam width for extended coverage

FEATURES

- > Rugged, military tested construction
- > Low power requirements
- > All-weather use
- > Scalable, lightweight & portable
- > Simple to operate: increased coverage with a single operator
- > Safer alternative to non-lethal and kinetic measures
- > HD camera (optional): Attachable camera and mount for recording video and audio during LRAD operation

MARKETS SERVED

- > Law Enforcement
- > Defense
- > Commercial Security
- > Critical Infrastructure Security
- > Maritime
- > Homeland Security
- > Fire Rescue & Incident Management
- > Port & Border Security
- > Emergency Warning
- > Mass Communication
- > Wildlife Preservation & Control



450XL

The Loudest, Longest Range Midsize Acoustic Hailing Device

LOW PROFILE, LONG RANGE COMMUNICATION SYSTEM

The LRAD 450XL utilizes technology developed and patented* by Genasys Inc. to provide the audio output of larger acoustic hailers almost twice its size and weight, while delivering the same outstanding vocal clarity inherent in all LRAD systems.

The LRAD 450XL broadcasts powerful warning tones to command attention to the highly intelligible voice messages that follow, enabling operators to change behavior and enhance response capabilities with safe, scalable escalation of force.

Lightweight and designed for use on tripods or mounted on vessels, vehicles, and Remote Weapon Stations (RWS), the LRAD 450XL is a highly effective, long range communication system in use around the world for public safety, law enforcement, maritime and defense applications.

*U.S. Patent No. 9,693,148



ACOUSTIC PERFORMANCE

Maximum Peak Output	150 dB SPL @ 1 meter, C-weighted
Maximum Continuous Output	145 dB SPL @ 1 meter, A-weighted
Sound Projection	+/- 15° @ 1 kHz / -3 dB
Communication Ranges	Maximum range up to 1,700 meters in ideal conditions. Operational range up to 500 meters over 88 dB of background noise. Ranges based on continuous output.

ENVIRONMENTAL PERFORMANCE

Cold/Hot Operating Temperature	MIL-STD-810G, Method 501.5 & 502.5, Procedure II, -33° to 60° C
Cold/Hot Storage Temperature	MIL-STD-810G, Method 501.5 & 502.5, Procedure I, -40° to 70° C
Operating Humidity	MIL-STD-810G, Method 507.5, Procedure II, Aggravated Cycle
Rain	MIL-STD-810G, Method 506.5, Procedure I, Blowing Rain
Salt Fog	MIL-STD-810G, Method 509.5
Shipboard Vibration	MIL-STD-167-1A
Random Vibration	MIL-STD-810G, Method 514.6, Wheeled Vehicles
Shipboard Shock	MIL-S-901D, Shipboard Shock, Class I, Shock grade B, Type A shock test
SRS Shock	MIL-STD-810G, Method 516.6, Procedure I, Functional shock
Safety	Designed to meet MIL-STD-1474D

MECHANICAL SPECIFICATIONS

Dimensions	14.5" H x 27" W x 11.6" D (36.8 cm x 68.6 cm x 29.5 cm)
Weight	36.5 lbs. (16.6 kg) without accessories
Construction	Molded low smoke composite, 6061 aluminum, 316 stainless hardware

ELECTRICAL REQUIREMENTS

Power Consumption	Normal Power Consumption for Voice Broadcasts: 55 Watts Normal Power Consumption for Alert Tone: 330 Watts
Power Input	12-28 VDC
Electromagnetic Compatibility (EMC)	FCC Part 15 class A radiated emissions

Designed to meet FCC Part 15 class A

Genasys

Global Provider of Protective Communications Solutions

Protecting people and saving lives for over 40 years, Genasys Protect covers more than 100 Million people in over 100 countries worldwide, including more than 550 U.S. cities.

For more information, visit genasys.com.

SCAN FOR VIDEO



LRAD products are available for purchase through multiple channels including: DLA TLS SOE, GSA Advantage, Federal and State grants, FEMA Authorized Equipment List (AEL), and others. More information: sales@genasys.com

© 2024 GENASYS INC.

D00101 Rev. F